

Price List for JZJ Spray Booth

No.	Item	Description	Unit (set)	Loading Capacity
1	JZJ-8000-AU	Spray Booth	1	1*20GP

Please check below specification for your reference, We can quote based on your requirement!

Model: JZJ-8000-AU

Outside Dimension (mm)	7006*5710*3420(L*W*H)	Inside Dimension(mm)	6900*4000*2650(L*W*H)
Front Door(mm)	3000*2600(W*H)	Service Door (mm)	800*2000(W*H)
Total Power	17KW		
Cabin System	Wall panel	50mm rock-wool sandwich panel, double face steel sheet thickness: 0.6mm	
	Ceiling panel	Galvanized steel sheet.	
	Basement	300mm depth, middle with grids, side with checkered plates.	
	Ramp	Three pieces 2000*900mm ramps	
	Glass	5mm safety tempered glass	
	Windows	Square glass windows.	
Air Make-up System	Air inlet fan system	1*7.5kw turbo fan, ABB/Siemens motor	
	Exhausted fan system	1*7.5kw turbo fan, ABB/Siemens motor	
	Air capacity	25000m ³ /h	
	Air control method	Air inlet system and exhausted system, each with 1 manual damper	
	Air ducting	8 meters air duct, one flop damper and one weather hood	
Purification System	Pre-filter	G3 grade, Pocket filter	
	Ceiling filter	EU5 / F5	
	Floor filter	Green fiber glass filter / G3 grade	
	Exhausted fan filters	Pocket filter and active carbon	
Heating System	Heat exchanger	SUS304 material, argon arc welding.	
	Heating burner:	Riello G20 diesel burner	
	Heating productivity	180000Kcal/h	
	Spray to baking switch	20N BELLIMO brand Electrical Damper	
	Chimney ducting	3 meters stainless ducting and one chimney cap	
	Max heating temperature	80°C	
	Heating time	4-6min(20-60°C)	
	fuel consumption	5-6L/vehicle	
Lighting System	Ceiling lights	10 Units, each 4 * 18W LED lamps. Total 720 W	
	Side lights	8 Units, each 2 * 18W LED lamps, Total 288W	
	Illumination	1000LUX	
Controlling System	Switched control panel	Spraying & baking switch, before baking flash-off, after baking flash off, lighting switch, emergency stop, breakdown alarm, failure alarm	